

KEY OR ELECTRONIC LOCK

MODEL SHOWN: TRIFORCE GRADE V M-245

# TRIFORCE GRADE VI

## BURGLARY, FIRE & EXPLOSION-RESISTANT PROTECTION

RATINGS: CASH £150,000 • VALUABLES £1.5m

### KEY FEATURES

- Burglary resistance in accordance with the updated and more stringent European standard, EN 1143-1:2019 T2, as certified by ECB•S for Grade IV, V and VI. Meets the demands of all Insurance Companies when it comes to burglary resistance.
- Tested by an independent, ISO 17025 accredited laboratory according to the NT Fire 017 – 60 Paper standard with certification managed by ECB•S. Protects your vital documents from the affects of fire.
- Protection against explosives in Grade IV EX to VI EX. Certified by ECB•S in accordance with the stringent European standard, EN 1143-1.
- Optional Planar Protection is a fully integrated, alarm wiring matrix within the safe body. Designed to be connected up to existing in-situ security systems, Planar Protection activates should any attempt to force entry through the body take place.
- Safes with Planar Protection are delivered fully prepared for alarm system connection and provide an additional deterrent to the would be thief.
- Optional Core Drill (CD) protection is available whilst at the same time retaining fire protection, an industry first.
- Supplied with two locks as standard with the option of a factory fitted electronic lock. This gives the flexibility to customise how TriForce T2 can be secured and operated.
- Ergonomic soft-touch handle and a range of internal fittings to maximise storage capacity.



### PRODUCT SPECIFICATIONS

Model	External Sizes (mm)			Internal Sizes (mm)			Volume (litres)	Weight (kg)	Shelves Included
	Height	Width	Depth	Height	Width	Depth			
M-95	994	594	604	790	390	303	95	824	2
M-245	994	844	784	790	640	483	245	1283	2
M-405	1514	844	784	1310	640	483	405	1834	3
M-520	1894	844	784	1690	640	483	520	2201	4
M-885	1894	1294	784	1690	1090	483	885	3164	4
M-1090	1894	1544	784	1690	1340	483	1090	3625	4

External dimensions exclude handle and hinge projections. In line with certification, weights can vary by +/- 5%.