



# INSAFE GRADE I

A BURGLARY RESISTANT SAFE



WATCH VIDEO



## KEY FEATURES

- Popular for home and commercial use
- Tested and Certified by LPCB to EN 1143-1 Grade I
- Approved by the Association of Insurance Surveyors
- Constructed using Fire Resistant Materials
- Base & rear fixing: supplied with an anchoring kit. Model 15 includes base and rear fixing
- Adjustable shelf/shelves

## LOCKING OPTIONS

Key Lock: EN 1300-Certified Class A  
Electronic Lock: EN 1300-Certified Class B

## PRODUCT SPECIFICATIONS

| Model | Product Code | External Sizes (mm) |       |        | Internal Sizes (mm) |       |       | Volume (litres) | Weight (kg) | Shelves Included |
|-------|--------------|---------------------|-------|--------|---------------------|-------|-------|-----------------|-------------|------------------|
|       |              | Height              | Width | Depth* | Height              | Width | Depth |                 |             |                  |
| 15K   | IGB-G1-15K   | 420                 | 320   | 320    | 320                 | 320   | 175   | 13              | 80          | 1                |
| 20K   | IGB-G1-20K   | 455                 | 405   | 370    | 355                 | 305   | 180   | 20              | 98          | 1                |
| 35K   | IGB-G1-35K   | 455                 | 455   | 465    | 355                 | 355   | 275   | 35              | 118         | 1                |
| 40K   | IGB-G1-40K   | 585                 | 405   | 465    | 485                 | 305   | 275   | 41              | 131         | 1                |
| 110K  | IGB-G1-110K  | 685                 | 520   | 615    | 585                 | 420   | 425   | 105             | 207         | 2                |
| 140K  | IGB-G1-140K  | 800                 | 550   | 640    | 700                 | 450   | 450   | 142             | 247         | 2                |
| 240K  | IGB-G1-240K  | 1000                | 610   | 715    | 900                 | 510   | 525   | 240             | 337         | 2                |
| 300K  | IGB-G1-300K  | 1200                | 610   | 707    | 1100                | 510   | 525   | 295             | 372         | 3                |
| 350K  | IGB-G1-350K  | 1400                | 610   | 707    | 1300                | 510   | 525   | 348             | 403         | 3                |

\*Add 50mm to external depth dimensions for hinges, handles and electronic lock projection